

The new XLR lavaller microphones require phantom power from the device they are plugged into. This document explains the process of enabling phantom power on the Zoom H4n recorders.

1. Plug in the wired XLR lavaller microphone to either of the XLR plugs on the bottom of the Zoom recorder.



2. Turn on the Zoom using the slider on the left-hand side. Slide then release.



3. Push the menu button on the right-hand side of the Zoom.



4. Use the click wheel above the menu button to scroll down to the INPUT option. Push the wheel inwards to select this menu.



5. Use the click wheel to scroll down to PHANTOM and push the wheel in again to bring up the phantom power options.



6. Use the click wheel to select the +48V option. ***DO NOT select +24V, this setting will not work with our microphones and could damage them if selected.***



The new XLR lavaller microphones require phantom power from the device they are plugged into. This document explains the process of enabling phantom power on the Zoom H4n recorders.

1. Plug in the wired XLR lavaller microphone to either of the XLR plugs on the bottom of the Zoom recorder.



2. Turn on the Zoom using the slider on the left-hand side. Slide then release.



3. Push the menu button on the right-hand side of the Zoom.



4. Use the click wheel above the menu button to scroll down to the INPUT option. Push the wheel inwards to select this menu.



5. Use the click wheel to scroll down to PHANTOM and push the wheel in again to bring up the phantom power options.



6. Use the click wheel to select the +48V option. ***DO NOT select +24V, this setting will not work with our microphones and could damage them if selected.***

